



013B

BIT HOLZSPIRALBOHRER WOOD TWIST DRILL HEX SHANK BITS



D	NL	GL	S	EAN	ART.-NR.
3	23	60	1/4" 6-kant	9002696176190	013B030060
3	33	70	1/4" 6-kant	9002696176206	013B030070
4	28	60	1/4" 6-kant	9002696176220	013B040060
4	42	75	1/4" 6-kant	9002696176237	013B040075
5	31	60	1/4" 6-kant	9002696176251	013B050060
5	56	85	1/4" 6-kant	9002696176268	013B050085
6	31	60	1/4" 6-kant	9002696176282	013B060060
6	66	95	1/4" 6-kant	9002696176299	013B060095
7	31	60	1/4" 6-kant	9002696176312	013B070060
7	81	110	1/4" 6-kant	9002696176329	013B070110
8	31	60	1/4" 6-kant	9002696176343	013B080060
8	81	110	1/4" 6-kant	9002696176350	013B080110
10	31	60	1/4" 6-kant	9002696176404	013B100060
10	81	110	1/4" 6-kant	9002696176411	013B100110
12	31	60	1/4" 6-kant	9002696179696	013B120060
12	81	110	1/4" 6-kant	9002696176459	013B120110

Ausführung: Holzspiralbohrer aus hochlegiertem Stahl, mit Zentrierspitze, 2 Schneiden und 2 Vorschneidern. Optimale Vorschneider in gezogener Ausführung sorgen für das Niederziehen und Durchtrennen der Holzfasern, bevor das Loch gebohrt wird. Eine Rückenfase verhindert das Abweichen des Durchmessers (bis zu 1500 Löcher ohne Nachschärfen).

Verwendung: Zum Bohren von Löchern in alle Arten von Hölzern, verleimte Hölzer sowie MDF und Acrylglas.

Characteristics: These wood twist drills are featuring high alloyed steel quality, with center point, 2 cutters and 2 spurs. Optimized spurs in special version ensure fast and easy cutting of the wood fibres before the hole is drilled. Additionally, a bevelled edge leads to a perfect drilling of the diameter without any deviation. The alloyed steel improves the stability time of the drill, up to 1500 holes without resharping are possible.

Usage: Best qualified for boring into all types of wood, laminated boards,